





GAUGES - LIQUID

4" X 1/2" MOUNT -STEEL CASE / BRASS INTERNALS

FEATURES & APPLICATIONS:

• Used in hydraulic and pneumatic systems, compressors, regulator machine, and suitable for fluid medium or gaseous which does not clog connection port or corrode stainless steel. Can use for severe service conditions where pulsation or vibration exist. Premium quality and long life.

Case Venting: Liquid filled gauges should be vented to atomosphere to relief internal case pressure prior to use. You can easly do this by turning the valve lever on the back of the gauage to the open position. Liquid-Fill gauges are typically shipped with the valve in the closed position.

TECHNICAL DATA:

- CASE: Stainless Steel
- WINDOW: Glass
- INTERNAL: Copper Alloy
- CONNECTION: Brass
- ACCURACY: ± 3/2/3% of span
- TEMPERATURE RANGE: -4°F to 140°F

STEEL CASE / BRASS INTERNALS

Face Size	Mount	PSI	Part #	Part #
4″	1/2" NPT		LM	UC
		15 psi / 103 kpa	G40151-1PS	
		30 psi / 200 kpa	G40301-1PS	
		60 psi / 400 kpa	G40601-1PS	
	1. Ale 1.	100 psi / 700 kpa	G401001-1PS	
		160 psi / 1,100 kpa	G401601-1PS	
		200psi / 1,400 kpa	G402001-1PS	
		300 psi / 2,100 kpa	G403001-1PS	
		400 psi / 2,800 kpa	G404001-1PS	
		600 psi / 4,000 kpa	G406001-1PS	
		1,000 psi / 7,000 kpa	G4010001-1PS	
		1,500 psi / 10,000 kpa		
		2,000 psi / 14,000 kpa	G4020001-1PS	
		3,000 psi / 21,000 kpa	G4030001-1PS	
		5,000 psi / 35,000 kpa	G4050001-1PS	
		6,000 psi / 70,000 kpa	G4060001-1PS	



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

Seal Fast.com