



GODZILLA ECON

FEATURES & APPLICATIONS:

• Designed for the delivery of fluids, resistant to many products such as oil, grease, acids, bases, salts, sewage & seawater.

• Irrigation - Agriculture - Pump Dis-charge -Industrial Wash Down

• Through the Weave Technology

- Less weight than Rubber Discharge
- 80% PVC 20% NBR

TECHNICAL DATA:

- **Temp Range:** -20° F to +176° F
- Cover: Ribbed, highly resistant to oil, abrasion and weathering

- Tube: Rubber liner
- Reinforcement: Ribbed, highly resistant to oil, abrasion and weathering
- Safety Factor: 3:1 min
- Branding:

BLACK NITRILE ECON								
ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Vacuum Rating "HG"	Part #
1-1/2"	.08″	200′	150	450	n/a	.21	n/a	Nitrile 10150E
2"	.08″	200′	150	450	n/a	.32	n/a	Nitrile 10200E
3"	.10″	200′	150	450	n/a	.48	n/a	Nitrile 10300E
4"	.10″	200′	150	450	n/a	.66	n/a	Nitrile 10400E
6"	.12″	200′	150	450	n/a	1.14	n/a	Nitrile 10600E
8"	.12″	100′	150	450	n/a	1.54	n/a	Nitrile 10800E
Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.								
sales@S	eal Fast.co	om	800.231.0734		Seal Fast.com		5603 Harvey Wilson Drive, Houston, TX 77020	