



STEAM



FEATURES & APPLICATIONS:

- High pressure wire reinforced steam hose designed for service w/Super heated steam in heat control, fire prevention, thawing, etc., In many industries at max pressure of 17 ATM (250 psi).
- Pin Prick Cover, for longer life drain after use.
- * NOT RECOMMENDED FOR STEAM CLEANER

NOTES:



WARNING:

- Drain after use
- Steam heat increases in temperature as pressure increases
- Please consult with your coupling manufacture to insure the hose is coupled in accordance with current safety standards.
- Exposer to steam can cause serious injury or even death.
- Correct hose selection, assembly, maintenance and useage is critical to avoid serious injury or even death.

TECHNICAL DATA:

- **Temp Range:** -40° F to +450° F
- **Cover:** Nitrile (pinpricked)
- **Tube:** Black, smooth, EPDM rubber specially compounded to withstand saturated & super-heated steam
- **Reinforcement:** Plies of steel wire cord
- **Safety Factor:** 10:1 min
- **Branding:**



BLACK NEOPRENE / NITRILE

| ID | OD | Length | Working Pressure | Burst Pressure | Bend Radius | lbs per ft. | Part # |
|--------|-------|------------|------------------|----------------|-------------|-------------|--------|
| 1/2" | .99" | 50" / 100' | 250 | n/a | 6" | .37 | ST 050 |
| 3/4" | 1.25" | 50" / 100' | 250 | n/a | 9" | .52 | ST 075 |
| 1" | 1.50" | 50" / 100' | 250 | n/a | 12" | .65 | ST 100 |
| 1-1/4" | 1.80" | 50" / 100' | 250 | n/a | 15" | .83 | ST 125 |
| 1-1/2" | 2.12" | 50" / 100' | 250 | n/a | 18" | 1.11 | ST 150 |
| 2" | 2.60" | 50" / 100' | 250 | n/a | 24" | 1.50 | ST 200 |