



WATER

**BLENDED WATER SUCTION**



**FEATURES & APPLICATIONS:**

- Designed to meet almost all water hose applications, especially designed for use in construction, mining, industrial, & agricultural service. It is flexible & with stands high vacuum.

**TECHNICAL DATA:**

- **Temp Range:** -22° F to +180° F
- **Cover:** Black, NR/SBR
- **Tube:** Black, NR/SBR
- **Reinforcement:** High tensile textile fabric; steel wire helix
- **Safety Factor:** 3:1 min
- **Branding:**



**BLACK SBR / NATURAL RUBBER**

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1"	1.37"	100'	150	600	5"	0.50	CWS 100 100
1-1/4"	1.65"	100'	150	600	5"	0.60	CWS 125 100
1-1/2"	1.89"	50' / 60' / 100'	150	600	6"	0.82	CWS 150 50
2"	2.44"	100'	150	600	8"	1.01	CWS 200 50
2-1/2"	3.00"	100'	150	600	10"	1.50	CWS 250 50
3"	3.55"	100'	150	600	12"	1.75	CWS 300 50
4"	4.57"	100'	150	400	16"	2.40	CWS 400 50
6"	6.61"	100'	150	400	24"	4.84	CWS 600 20
8"	8.70"	100'	150	400	32"	8.10	CWS 800 20