

PIPE FITTINGS



& VALVES

VALVES

BALL - BRASS LEAD FREE UL 600 WOG/CWP

FEATURES & APPLICATIONS:

- Standard Port 2 Piece
- 600 WOG/CWP
- Lead Free
- Plumbing or heating projects, low pressure steam, compressed air, HVAC



TECHNICAL DATA:

- **WOG** = Rating indicates the maximum non-shock pressure at ambient temperatures at which the valve may be used.
- **CWP** = Cold working pressure


WOG: Water, Oil & Gas: This was an older, generic pressure rating call-out which has been largely replaced by CWP. In this designation, GAS" refers to any non-flammable, compressible fluid in a gaseous state. It does not imply a product's suitability or third-party approval for use with flammable gases. Similarly, in this designation, "Oil" does not imply a product's third-party approval for use with any petroleum products.

BRASS					
Size	Part #				
1/4"	BFVLF 025				
3/8"	BFVLF 038				
1/2"	BFVLF 050				
3/4"	BFVLF 075				
1"	BFVLF 100				
1-1/4"	BFVLF 125				
1-1/2"	BFVLF 150				
2"	BFVLF 200				
2-1/2"	BFVLF 250				
3"	BFVLF 300				
4"	BFVLF 400				




PIPE FITTINGS





Dimensions							
Size	G	В	Н	D	L	Part #	
1/4"	1/4" NPT	3.15	1.50	.35	1.57	BFVLF 025	
3/8"	3/8" NPT	3.15	1.61	.39	1.52	BFVLF 038	
1/2"	1/2" NPT	3.54	1.81	.55	1.87	BFVLF 050	
3/4"	3/4" NPT	3.54	2.13	.75	2.17	BFVLF 075	
1"	1" NPT	4.33	2.17	.87	2.44	BFVLF 100	
1-1/4"	1-1/4" NPT	5.12	2.56	1.14	2.91	BFVLF 125	
1-1/2"	1-1/2" NPT	5.43	2.95	1.46	3.31	BFVLF 150	
2"	2" NPT	7.13	3.35	1.77	3.86	BFVLF 200	
2-1/2"	2-1/2" NPT	9.25	4.72	2.20	5.47	BFVLF 250	
3"	3" NPT	9.25	4.92	2.72	5.67	BFVLF 300	
4"	4" NPT	9.25	5.51	3.35	6.65	BFVLF 400	



DISCLAIMER All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast Inc. cannot guarantee the dimensions will exactly match those in the drawing. The drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited. DRAWING NOT TO SCALE MATERIAL BRASS BRASS

