

PIPE FITTINGS



VALVES

BALL - LOCKING HANDLE 304 SS 1000 WOG/CWP

FEATURES & APPLICATIONS:

- Standard Port 1 Piece
- 1000 WOG/CWP
- 304 SS PTFE Seat
- Locking Handle
- Plumbing or heating projects, low pressure steam, compressed air, HVAC



TECHNICAL DATA:

- **WOG** = Rating indicates the maximum non-shock pressure at ambient temperatures at which the valve may be used.
- **CWP** = Cold working pressure

WOG: Water, Oil & Gas: This was an older, generic pressure rating call-out which has been largely replaced by CWP. In this designation, GAS" refers to any non-flammable, compressible fluid in a gaseous state. It does not imply a product's suitability or third-party approval for use with flammable gases. Similarly, in this designation, "Oil" does not imply a product's third-party approval for use with any petroleum products.


304 SS					
Size	Part #				
1/4"	SV 025SS304				
3/8"	SV 038SS304				
1/2"	SV 050SS304				
3/4"	SV 075SS304				
1"	SV 100SS304				
1-1/4"	SV 125SS304				
1-1/2"	SV 150SS304				
2"	SV 200SS304				
2-1/2"	SV 250SS304				
3"	SV 300SS304				




PIPE FITTINGS







Dimensions						
Size	E	Н	D	L	Part #	
1/4"	2.44	2.05	.59	3.94	SV 025SS304	
3/8"	2.44	2.05	.59	3.94	SV 038SS304	
1/2"	2.44	2.05	.59	3.94	SV 050SS304	
3/4"	2.76	2.36	.79	4.72	SV 075SS304	
1"	3.73	2.76	.98	5.51	SV 100SS304	
1-1/4"	3.54	2.95	1.26	5.51	SV 125SS304	
1-1/2"	4.17	3.43	1.50	7.09	SV 150SS304	
2"	4.86	3.82	1.93	7.09	SV 200SS304	
2-1/2"	5.71	5.12	2.56	8.82	SV 250SS304	
3"	6.49	5.83	3.15	8.82	SV 300SS304	



BALL VALVE w/Locking Handle - 1000 WOG/CWP

DISCLAIMER

All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast Inc. cannot guarantee the dimensions will exactly match those in the drawing. The drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

THE SIMPLE SOLUTION

DRAWING NOT TO SCALE

PART #

MATERIAL

SV....SS304

STAINLESS STEEL 304