



**90°  
ELBOW  
TYPE DA**

**FEATURES & APPLICATIONS:**

• **General Uses:**

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transferred.

Size	Working PSI	D1	D2	D3	D4	W	H	H1	PART #
1-1/2"	150	2.571	2.122	1.689	2.102	3.465	3.347	3.278	DA150AL90
2"	150	2.992	2.508	2.063	2.484	3.780	6.142	4.921	DA200AL90
2" X 3"	150	2.992	2.508	3.201	3.602	3.780	6.646	5.016	DA2030AL90
3"	150	4.154	3.626	3.201	3.602	5.079	7.284	5.650	DA300AL90
3" X 2"	150	4.154	3.626	2.063	2.484	5.118	4.843	4.921	DA3020AL90
3" X 4"	150	4.154	3.626	4.307	4.705	5.079	8.169	5.882	DA3040AL90
4"	150	5.354	4.732	4.307	4.705	6.181	9.921	7.598	DA400AL90
4" X 3"	150	5.354	4.732	3.201	3.602	6.181	7.748	6.358	DA4030AL90
6"	75	7.579	6.949	6.358	6.925	8.898	7.795	8.171	DA600AL90

**WARNING:** Cam & Groove Couplings should NOT be used with any compressed gas, including steam or air. Metal fittings should NOT be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are NOT designed for pressure applications.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TITLE <b>TYPE DA 90°</b>	
<p><b>DISCLAIMER</b></p> <p>All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.</p>	<p>MATERIAL</p> <p><b>A226AL</b></p>
<p><b>DRAWING NOT TO SCALE</b></p>	<p>PART #</p> <p><b>DA...AL90</b></p>

