



TYPE DA

Size	PSI	D1	D2	D3	W	H	PART #
1-1/2" x 1"	150	2.500	2.122	2.480	3.504	5.118	DA1520SS
1-1/2" x 2"	150						DA1520SS
2" x 1"	150	2.665	2.508	1.449	3.780	5.118	DA2010SS
2" x 1-1/2"	150	2.665	2.508	2.102	3.780	4.803	DA2015SS
2" x 2"	150	2.665	2.508	2.480	3.780	5.118	DA2020SS
2" x 3"	150	2.894	2.508	3.602	3.780	5.512	DA2030SS
2" x 4"	150						DA2040SS
2-1/2" x 2"	150						DA2520SS
3" x 1-1/2"	150						DA3015SS
3" x 2"	150	4.095	3.626	4.480	5.079	5.551	DA3020SS
3" x 3"	150	4.095	3.626	3.602	5.079	5.689	DA3030SS
3" x 4"	150	4.134	3.626	4.705	5.102	5.965	DA3040SS
4" x 2"	150	5.197	4.732	2.484	6.181	5.354	DA4020SS
4" x 2-1/2"	150						DA4025SS
4" x 3"	150	5.197	4.732	3.602	6.181	5.354	DA4030SS
4" x 6"	150						DA4060SS
6" x 4"	75	7.579	6.949	4.705	8.898	6.811	DA6040SS

FEATURES & APPLICATIONS:

• **General Uses:**

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transferred.

WARNING: Cam & Groove Couplings should NOT be used with any compressed gas, including steam or air. Metal fittings should NOT be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are NOT designed for pressure applications.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TITLE TYPE DA - FEMALE COUPLER X MALE ADAPTER REDUCING	
DISCLAIMER All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.	MATERIAL SUS 316
DRAWING NOT TO SCALE	PART # DA...SS

