


TYPE DA-



DD...-1SS, -2SS, -3SS

FEATURES & APPLICATIONS:

• General Uses:

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transfered.

Size	Norking Norking	D1	D2	D3	W1	W2	Н	T	PART #
2" X 2" X 1/2" NPT	150	2.894	2.508	2.480	3.780	4.063	5.630	1/2" NPT	DA2020SS-1SS
2" X 2" X 3/4" NPT	150	2.894	2.508	2.480	3.780	4.063	5.630	3/4" NPT	DA2020SS-2SS
3" X 2" X 1/2" NPT	150	4.095	3.626	2.480	5.079	5.118	6.102	1/2" NPT	DA3020SS-1SS
3" X 2" X 3/4" NPT	150	4.095	3.626	2.480	5.079	5.118	6.102	3/4" NPT	DA3020SS-2SS
3" X 2" X 1" NPT	150								DA3020SS-3SS
3" X 3" X 1/2" NPT	150	4.095	3.626	3.602	5.079	5.197	5.689	1/2" NPT	DA3030SS-1SS
3" X 4" X 1/2" NPT	150	4.134	3.626	4.705	5.185	5.799	6.496	1/2" NPT	DA3040SS-1SS
3" X 4" X 3/4" NPT	150	4.134	3.626	4.705	5.185	5.799	6.496	3/4" NPT	DA3040SS-2SS
4" X 3" X 1/2" NPT	150	5.197	4.732	3.602	6.295	5.799	5.965	1/2" NPT	DA4030SS-1SS
4" X 3" X 3/4" NPT	150	5.197	4.732	3.602	6.295	5.799	5.965	3/4" NPT	DA4030SS-2SS

WARNING: Cam & Groove Couplings should **NOT** be used with any compressed gas, including steam or air. Metal fittings should **NOT** be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are **NOT** designed for pressure applications.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TYPE DA- - FEMALE COUPLER X MALE ADAPTER REDUCING W/PIPE TAPE

DISCLAIMER

All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

SUS 316

DRAWING NOT TO SCALE

PART # DA-...SS

MATERIAL



sales@sealfast.com 800.231.0734

sealfast.com