







FEATURES & APPLICATIONS:

• General Uses:

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transfered.

Size	Norking Norking	D1	D2	D3	D4	Н	W	PART #
2"	150	0.394	2.450	2.400	0.189	2.382	2.484	AW 200SSI
3"	150	0.394	3.580	3.535	0.189	2.551	3.602	AW 300SSI
4"	150	0.394	4.685	4.530	0.189	2.677	4.705	AW 400SSI
6"	75	0.394	6.655	6.217	0.189	3.150	6.929	AW 600SSI

WARNING: Cam & Groove Couplings should **NOT** be used with any compressed gas, including steam or air. Metal fittings should **NOT** be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are NOT designed for pressure applicaions.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TYPE AW

DISCLAIMER All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

DRAWING NOT TO SCALE

MATERIAL

SUS 316

PART# AW...SSI

