



## FEATURES & APPLICATIONS:

## • General Uses:

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transfered.

Size	Morking	D1	D2	D3	W	Н	PART #
1-1/2" x 1-1/2"	150						BLN1515SS
2" x 2"	150	2.894	2.508	2" NPT	4.547	3.858	BLN2020AL
3″ x 3″	150	4.134	3.626	3" NPT	5.512	5.146	BLN3030AL
4" x 4"	150	5.197	4.732	4" NPT	5.638	6.299	BLN4040AL

**WARNING:** Cam & Groove Couplings should **NOT** be used with any compressed gas, including steam or air. Metal fittings should **NOT** be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are **NOT** designed for pressure applications.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

## TITLE TYPE BLN - LONGNECK FEMALE X MALE NPT

 DISCLAIMER
 MATERIAL

 All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.
 MATERIAL

 DISCLAIMER
 All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.
 MATERIAL

 DRAWING NOT TO SCALE
 PART #
 BLN...SS

 sales@sealfast.com
 800.231.0734
 sealfast.com
 5603 Harvey Wilson Drive, Houston, TX 77020