



FEATURES & APPLICATIONS:

• General Uses:

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transfered.

Size	D1	D2	D3	Н	W	PART #
1-1/2" x 1"	2.500	2.122	1.032	4.406	3.508	CR1510SS
2" x 1-1/2"	2.661	2.508	1.520	4.595	3.819	CR2015SS
3" x 2"	4.134	3.626	2.016	5.248	5.106	CR3020SS
3" x 2-1/2"	4.134	3.626	2.520	5.626	5.106	CR3025SS
4" x 3"	5.197	4.732	3.016	6.528	6.299	CR4030SS

WARNING: Cam & Groove Couplings should NOT be used with any compressed gas, including steam or air. Metal fittings should NOT be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are **NOT** designed for pressure applicaions.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TYPE CR - FEMALE COUPLER X SHANK REDUCING C MATERIAL

DISCLAIMER

All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

PART#

CR...SS

SUS 316



DRAWING NOT TO SCALE

sealfast.com

800.231.0734

5603 Harvey Wilson Drive, Houston, TX 77020