



FEATURES & APPLICATIONS:

• General Uses:

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transfered.

Size	Working ISA	D1	D2	D3	W	W1	Н	H1	PART #
2″	150	3.016	2.508	2.390	3.661	2.697	3.177	0.394	DW 200AL
3″	150	4.244	3.626	3.532	4.921	3.890	3.768	0.394	DW 300AL
4″	150	5.492	4.732	4.530	6.126	4.976	3.969	0.394	DW 400AL
6″	75							0.394	DW 600AL

WARNING: Cam & Groove Couplings should NOT be used with any compressed gas, including steam or air. Metal fittings should NOT be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are **NOT** designed for pressure applicaions. Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles. TITLE TYPE DW MATERIAL DISCLAIMER All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions A226AL in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited. I S L PART # DW...AL **DRAWING NOT TO SCALE** sealfast.com sales@sealfast.com 800.231.0734 5603 Harvey Wilson Drive, Houston, TX 77020