



GAUGES - LIQUID

2-1/4" X 1/4" FRONT PANEL MOUNT
STEEL CASE / SS INTERNALS

FEATURES & APPLICATIONS:

- Used in hydraulic and pneumatic systems, compressors, regulator machine, and suitable for fluid medium or gaseous which does not clog connection port or corrode stainless steel. Can use for severe service conditions where pulsation or vibration exist. Premium quality and long life.

Case Venting: Liquid filled gauges should be vented to atmosphere to relief internal case pressure prior to use. You can easily do this by turning the valve lever on the back of the gauge to the open position. Liquid-Fill gauges are typically shipped with the valve in the closed position.



CBM
Center back mount

TECHNICAL DATA:

- CASE: Stainless Steel
- WINDOW: Poly Carbonate
- INTERNAL: Stainless Steel
- CONNECTION: Stainless Steel 2 pieces
- ACCURACY: ± 1.6% of full scale
- TEMPERATURE RANGE: -4°F to 140°F

ALL STAINLESS STEEL

Face Size	Mount	PSI	Part #
2-1/2"	1/4" NPT		CMB
		15 psi / 103 kpa	FFG25152PSSU
		30 psi / 200 kpa	FFG25302PSSU
		60 psi / 400 kpa	FFG25602PSSU
		100 psi / 700 kpa	FFG251002PSSU
		160 psi / 1,100 kpa	FFG251602PSSU
		200psi / 1,400 kpa	FFG252002PSSU
		300 psi / 2,100 kpa	FFG253002PSSU
		400 psi / 2,800 kpa	FFG254002PSSU
		600 psi / 4,000 kpa	FFG256002PSSU
		800 psi / 5,500 kpa	FFG258002PSSU
		1,000 psi / 7,000 kpa	FFG2510002PSSU
		1,500 psi / 10,000 kpa	FFG2515002PSSU
		2,000 psi / 14,000 kpa	FFG2520002PSSU
3,000 psi / 21,000 kpa	FFG2530002PSSU		
5,000 psi / 35,000 kpa	FFG2550002PSSU		

2-1/2"

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.