



**CRIMP
TYPE C**

FEATURES & APPLICATIONS:

• **General Uses:**

A camlock fitting is a type of coupling that is used to connecting hose and or pipes together that transfers liquids, powders and granules. A straight through connection is made that maintains the pipe size and allows the free flow of materials being transferred.

Size	Working PSI	D1	D2	D3	D4	D5	D6	H	W	PART #
1"	150	1.835	1.465	1.032	0.972	0.728	1.583	4.095	2.598	C100BRC
1-1/2"	150	2.571	2.122	1.520	1.445	1.591	2.677	5.146	3.780	C150BRC
2"	150	2.992	2.508	2.016	1.917	1.591	2.677	5.146	3.780	C200BRC
2-1/2"	150	3.465	3.008	2.520	2.421	2.035	3.161	5.673	4.409	C250BRC
3"	150	4.154	3.626	3.016	2.933	2.563	3.839	6.555	5.106	C300BRC
4"	150	5.335	4.732	4.019	3.917	3.445	4.969	6.886	6.181	C400BRC
6"	75	7.579	6.949	6.055	5.929	5.429	7.201	8.551	8.898	C600BRC

WARNING:

Cam & Groove Couplings should **NOT** be used with any compressed gas, including steam or air. Metal fittings should **NOT** be used with Polypropylene Cam & Groove. Dust Caps and Dust Plugs are **NOT** designed for pressure applications.

Note: All Seal Fast Cam & Groove Stainless Bodies are 316 Investment with 304 Handles.

TITLE CRIMPTEK TYPE C - FEMALE COUPLER X SHANK

<p>DISCLAIMER</p> <p>All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions in the drawing will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.</p>	<p>MATERIAL</p> <p>BRASS</p>
	<p>PART #</p> <p>C...BRC</p>
<p>DRAWING NOT TO SCALE</p>	

