



## WATER - LW

EPDM PVC SUCTION

### FEATURES & APPLICATIONS:

- Heavy-duty liquid suction hose ideal for construction, de-watering, liquid waste, cess pool, septic, agricultural, & marine use. Hose is designed to remain flexible in winter conditions. lightweight, & external provides for easy drag. The smooth interior provides for optimum product flow.

- Flexible for easy handling &



### TECHNICAL DATA:

- Temp Range: -40° F to +180° F
- Cover: Black EPDM w/Green Polypropylene Helix
- Tube: Black Thermoplastic Rubber
- Reinforcement: Rigid Lime Green Polypropylene Helix
- Safety Factor: 3:1 min
- Branding:

#### EPDM TUBE / PVC HELIX

ID	OD	Length	Working Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	1.84"	100'	50	3.2"	0.40	LW- 150
2"	2.43"	20'/25'/33'/100'	50	5.1"	0.67	LW- 200
3"	3.52"	20'/25'/33'/100'	43	7.1"	1.10	LW-300
4"	4.62"	100'	38	11"	1.84	LW-400



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this page.