



WATER

WATER BLUE MAMBA
STANDARD DUTY DISCHARGE



FEATURES & APPLICATIONS:


- Designed for water discharge applications in agriculture, construction, industry. Strong, lightweight discharge hose. Rolls up flat for easy storage. The working pressure ratings are based on ambient temperature of 70° F & will vary inversely with temperature changes.

TECHNICAL DATA:

- **Temp Range:** -5° F to +130° F
- **Cover:** Blue PVC
- **Tube:** Blue PVC
- **Reinforcement:** 2 spiral plies
- **Safety Factor:** 3:1 min
- **Branding:**

BLUE PVC

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per 100 ft.	Weight Per Roll	Part #
1"	---	300'	70	210	n/a	.107	32	LD 100
1-1/4"	---	300'	70	210	n/a	.127	38	LD 125
1-1/2"	---	300'	70	210	n/a	.14	42	LD 150
2"	---	300'	65	195	n/a	.20	60	LD 200
2-1/2"	---	300'	55	165	n/a	.26	78	LD 250
3"	---	300'	55	165	n/a	.30	90	LD 300
4"	---	300'	55	150	n/a	.40	120	LD 400
5"	---	300'	50	120	n/a	.57	171	LD 500
6"	---	300'	40	120	n/a	.75	225	LD 600
8"	---	300'	40	120	n/a	.110	330	LD 800
10"	---	100'	40	105	n/a	.181	181	LD 1000
12"	---	100'	35	90	n/a	.195	195	LD 1200

 Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.