



SEALFAST
THE SIMPLE SOLUTION

HOSES
THERMOPLASTIC



WATER

GODZILLA 10

NITRILE 10

FEATURES & APPLICATIONS:

- Designed for the delivery of fluids, resistant to many products such as oil, grease, acids, bases, salts, sewage & seawater.
- Irrigation - Agriculture - Pump Discharge - Industrial Down
- Through the Weave Technology
- Less weight than Rubber Discharge
- 70% PVC / 30% NBR

TECHNICAL DATA:

- **Temp Range:** -4° F to +176° F
- **Cover:** Ribbed, highly resistant to oil, abrasion and weathering
- **Tube:** Nitrile-PVC oil/weather resistant rubber, polyester reinforcement
- **Reinforcement:** n/a
- **Safety Factor:** 3:1 min
- **Branding:**

BLACK NITRILE 10

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per 100 ft.	Weight Per Roll	Part #
1-1/2"	.08"	200'	200	150	n/a	21	42	Nitrile 10150
2"	.08"	200'	200	150	n/a	32	64	Nitrile 10200
2-1/2"	.08"	200'	200	150	n/a	44	88	Nitrile 10250
3"	.10"	200'	200	150	n/a	48	96	Nitrile 10300
4"	.10"	200'	200	150	n/a	66	132	Nitrile 10400
6"	.12"	200'	200	150	n/a	114	n/a	Nitrile 10600
8"	.12"	100'	200	150	n/a	154	154	Nitrile 10800
10"	.14"	100'	200	150	n/a	205	205	Nitrile 101000
12"	.14"	100'	200	150	n/a	220	220	Nitrile 101200



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

sales@Seal Fast.com

800.231.0734

Seal Fast.com

5603 Harvey Wilson Drive, Houston, TX 77020