



PETROLEUM

TANK TRUCK -
150 PSI



FEATURES & APPLICATIONS:

- Designed for transferring gasolines & petroleum products
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.

TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



BLACK NITRILE BLEND / NITRILE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1"	1.46"	100'	150	450	4"	.67	TT 100 100
1-1/4"	1.75"	100'	150	450	5"	.87	TT 125 100
1-1/2"	2.01"	60'	150	450	6"	.94	TT 150 100
2"	2.50"	60' / 100' / 200'	150	450	8"	1.34	TT 200 100
2-1/2"	3.03"	60' / 100'	150	450	10"	1.61	TT 250 100
3"	3.54"	60' / 100' / 200'	150	450	12"	2.02	TT 300 100
4"	4.67"	60' / 100' / 200'	150	450	16"	2.76	TT 400 100
6"	6.65"	20' / 25' / 100'	150	450	24"	5.51	TT 600 100
8"	8.88"	20'	100	300	32"	9.07	TT 800 100