



MILL - SINGLE JACKET
SBR LINED

FEATURES & APPLICATIONS:

- All synthetic, lightweight SBR (rubber) lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.



TECHNICAL DATA:

- **Temp Range:** -22° F to +185° F
- **Cover:** Single Jacket White Polyester
- **Tube:** SBR
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-SBR LINED

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
1"	n/a	50'	110	n/a	n/a	8	---	80-100
1-1/2"	n/a	50' / 100'	110	n/a	n/a	11 / 22	---	80-150 / 80-150 100
2"	n/a	50' / 100'	110	n/a	n/a	17 / 34	---	80-200 / 80-200 100
2-1/2"	n/a	50' / 100'	110	n/a	n/a	20 / 40	---	80-250 / 80-250 100
3"	n/a	50' / 100'	110	n/a	n/a	28 / 56	---	80-300 / 80-300 100
4"	n/a	50'	110	n/a	n/a	50	---	80-400