



**TECHNICAL DATA:**

- **Composition:** SBR
- 65 Duromete +/- 5
- **Elongation:** MIN 300%
- **Tensile Strength:** MIN 700 psi

**SKIRTBOARD**

SPECIFIC WIDTH

FEATURES & APPLICATIONS:

- Excellent abrasion & weather resistant
- Well suited for use as conveyor skirting, belt wipers, blast curtains & bumpers.

SBR

Thickness	Width	Avg. Length	Avg. Lbs per Roll	Part #
<b>1/4"</b>				
	3"	50'	20.5	140360
	4"	50'	27	140460
	5"	50'	34	140560
	6"	50'	40.5	140660
	8"	50'	54	140860
	10"	50'	67.5	141060
	12"	50'	81.5	141260
<b>3/8"</b>				
	3"	50'	30.5	380360
	4"	50'	40.5	380460
	5"	50'	50.5	380560
	6"	50'	61	380660
	8"	50'	81	380860
	10"	50'	101.5	381060
	12"	50'	121.5	381260
<b>1/2"</b>				
	4"	50'	54	120460
	5"	50'	67.5	120560
	6"	50'	81.5	120660
	8"	50'	108.5	120860
	10"	50'	135.5	121060
	12"	50'	162.5	121260
<b>3/4"</b>				
	3"	50'	61	340360
	6"	50'	122	340660
	8"	50'	162.5	340860
	10"	50'	203	341060
<b>1"</b>				
	6"	50'	162.5	100660
	8"	50'	217	100860
	10"	50'	271	101060
	12"	50'	325.5	101260
<b>1-1/2"</b>				
	10"	50'	406.5	151060



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.