



**TECHNICAL DATA:**

- **Composition:** Pure Gum
- 65 Duromete +/- 5
- **Elongation:** MIN 600%
- **Tensile Strength:** MIN 2500 psi

**PURE GUM SHEET**

TAN

**FEATURES & APPLICATIONS:**

- Particularly suited for applications where a soft rubber seal is necessary because applied pressure may be light to effect a satisfactory seal.

**NOTES:**

- Pure gum is a composition containing a high percentage of rubber & a minimum of other ingredients to produce vulcanization. It is generally recommended for use against hot & cold water.

**PURE GUM**

| Thickness | Width | Avg. Length | Lbs per Roll | Part #       |
|-----------|-------|-------------|--------------|--------------|
| 1/8"      | 36"   | 53'         | 100          | PU-GUM-4-36  |
|           | 48"   | 40'         | 100          | PU-GUM-4-48  |
| 3/16"     | 36"   | 71'         | 200          | PU-GUM-6-36  |
|           |       |             |              |              |
| 1/4"      | 36"   | 53'         | 200          | PU-GUM-8-36  |
|           | 48"   | 40'         | 200          | PU-GUM-8-48  |
| 3/8'      | 36"   | 35'         | 200          | PU-GUM-12-36 |
|           | 48"   | 13'         | 100          | PU-GUM-12-48 |
| 1/2'      | 36"   | 27'         | 200          | PU-GUM-16-36 |
|           | 48"   | 27'         | 275          | PU-GUM-16-48 |
| 3/4"      | 36"   | 18'         | 200          | PU-GUM-24-36 |
|           |       |             |              |              |
| 1"        | 36"   | 13'         | 200          | PU-GUM-32-36 |
|           |       |             |              |              |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.