



FIRE - SINGLE JACKET

RED NITRILE COVERED PERMALINE -

500# Test

FEATURES & APPLICATIONS:

- This covered hose is a premium quality, abrasion resistant, chemical resistant, lightweight industrial fire hose. The one-piece cover/lining totally encompasses the synthetic reinforcement providing a industrial fire hose that is easy to use, clean and maintain. This hose is totally immune to mildew & resists the effects of most chemicals. Recommended 225 psi working pressure.

TECHNICAL DATA:

- Temp Range:** -4° F to +174° F
- Cover:** Red, Nitrile
- Tube:** Nitrile
- Reinforcement:** n/a
- Safety Factor:** n/a
- Branding:**

NOTES:

- Maximum advised operating/working pressure that should not exceed 90% of Service Test Pressure (Stenciled on hose)

NITRILE - RED

ID	OD	Length	Working Pressure	Service Test Pressure	Bend Radius	Lbs per Roll	Bowl Size	Part #
1-1/2"	n/a	50'/100'	225	250	n/a	11/21	1-3/4"	PERMALINE150 / PERMALINE150 100
2-1/2"	n/a	50'/100'	225	250	n/a	20/40	2-13/16"	PERMALINE250 / PERMALINE250 100



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.