



**MATERIAL  
TRANSFER**

## DRY CEMENT DISCHARGE

### FEATURES & APPLICATIONS:

- A Soft wall hose suitable for dry abrasive materials & slurrie transfers.
- Compounded for long wear resistance in handling of hard, sharp, abrasive materials; anti-static.



### TECHNICAL DATA:

- **Temp Range:** -40° F to +158° F
- **Cover:** Black NR / SBR
- **Tube:** Black BR / SBR / NR
- **Reinforcement:** High tensile tire cord
- **Safety Factor:** 3:1 min
- **Branding:**



### BLACK BLENDED RUBBER

| ID | OD    | Length     | Working Pressure | Burst Pressure | Wall Thickness | lbs per ft. | Part #   |
|----|-------|------------|------------------|----------------|----------------|-------------|----------|
| 4" | 4.37" | 50' / 100' | 75               | 225            | 1/8"           | 1.61        | CH 400-1 |
|    | 4.63" | 50' / 100' | 75               | 225            | 3/16"          | 2.08        | CH 400-2 |
|    | 4.79" | 50' / 100' | 75               | 225            | 1/4"           | 2.49        | CH 400-3 |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.