



PETROLEUM

TANK TRUCK -
150 PSI



FEATURES & APPLICATIONS:

- Designed for transferring gasolines & petroleum products
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.

TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



BLACK NITRILE BLEND / NITRILE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1"	1.46"	100'	150	450	4"	.67	TT 100 100
1-1/4"	1.75"	100'	150	450	5"	.87	TT 125 100
1-1/2"	2.01"	60'	150	450	6"	.94	TT 150 100
2"	2.50"	60' / 100' / 200'	150	450	8"	1.34	TT 200 100
2-1/2"	3.03"	60' / 100'	150	450	10"	1.61	TT 250 100
3"	3.54"	60' / 100' / 200'	150	450	12"	2.02	TT 300 100
4"	4.67"	60' / 100' / 200'	150	450	16"	2.76	TT 400 100
6"	6.65"	20' / 100'	150	450	24"	5.51	TT 600 100
8"	8.88"	20'	100	300	32"	9.07	TT 800 20



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.