



PETROLEUM

**TANK TRUCK BLACK**  
CORRUGATED - 150 PSI



**FEATURES & APPLICATIONS:**

- Designed for transfer of gasoline, oil & other petroleum based products where maximum flexibility is needed; excellent kink resistance.
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.

**TECHNICAL DATA:**

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



**CROSS-LINKED POLYETHYLENE**

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	2.24"	100'	150	450	2"	.98	CTT 100 100
2"	2.64"	100'	150	450	2"	1.34	CTT 200 100
3"	3.66"	100'	150	450	3"	1.95	CTT 300 100
4"	4.76"	100'	150	450	4"	2.96	CTT 400 100

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.