



PETROLEUM

TANK TRUCK -
300 PSI



FEATURES & APPLICATIONS:

- Designed for transferring gasolines & petroleum products
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.

TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



BLACK NITRILE BLEND / NITRILE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	1.9"	100'	150	450	9"	0.7	TT 150-220
2"	2.5"	100'	150	450	12"	1.1	TT 200-220
3"	3.5"	100'	150	450	18"	1.8	TT 300-220
4"	4.6"	100'	150	450	24.1"	2.8	TT 400-220
6"	6.6"	100'	150	450	35.9"	5.3	TT 600-220
8"	8.7"	20'	150	450	48.2"	8.8	TT 800-220



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.