



SEALFAST
THE SIMPLE SOLUTION

HOSES
INDUSTRIAL RUBBER



PETROLEUM

TANK TRUCK RED

CORRUGATED - 150 PSI

FEATURES & APPLICATIONS:

- Designed for transfer of gasoline, oil & other petroleum based products where maximum flexibility is needed; excellent kink resistance.
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.



TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Red, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



CROSS-LINKED POLYETHYLENE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	2.24"	100'	150	450	2"	.98	CTT 100R 100
2"	2.64"	100'	150	450	2"	1.34	CTT 200R 100
3"	3.66"	100'	150	450	3"	1.95	CTT 300R 100
4"	4.76"	100'	150	450	4"	2.96	CTT 400R 100



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

sales@Seal Fast.com

800.231.0734

Seal Fast.com

5603 Harvey Wilson Drive, Houston, TX 77020