



**SEALFAST**  
THE SIMPLE SOLUTION

**HOSES**  
INDUSTRIAL RUBBER



PETROLEUM

## CRUDE OIL SUCTION

### FEATURES & APPLICATIONS:

- Designed for oilfield vacuum truck service. Tube & cover have resistance to crude oil.



### TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/NBR
- **Tube:** CR/NBR
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**

### NOTES:

- Recommended for CRUDE OIL ONLY. \*NOT RECOMMENDED FOR REFINED PETROLEUM PRODUCTS.



### NITRILE BLEND

| ID     | OD    | Length | Working Pressure | Burst Pressure | Bend Radius | lbs per ft. | Part #  |
|--------|-------|--------|------------------|----------------|-------------|-------------|---------|
| 1-1/2" | 1.89" | 100'   | 150              | 450            | 7"          | .80         | COS 100 |
| 2"     | 2.45" | 100'   | 150              | 450            | 8"          | 1.00        | COS 200 |
| 2-1/2" | 3.00" | 100'   | 150              | 450            | 10"         | 1.26        | COS 250 |
| 3"     | 3.50" | 100'   | 150              | 450            | 12"         | 1.80        | COS 300 |
| 4"     | 4.55" | 100'   | 150              | 450            | 15"         | 2.30        | COS 400 |
| 6"     | 6.61" | 20'    | 150              | 450            | 26"         | 5.00        | COS 600 |
| 8"     | 8.70" | 20'    | 150              | 450            | 35"         | 7.60        | COS 800 |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

sales@Seal Fast.com

800.231.0734

Seal Fast.com

5603 Harvey Wilson Drive, Houston, TX