



PETROLEUM

CRUDE OIL
SUCTION



FEATURES & APPLICATIONS:

- Designed for oilfield vacuum truck service. Tube & cover have resistance to crude oil.

TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/NBR
- **Tube:** CR/NBR
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**

NOTES:

- Recommended for CRUDE OIL ONLY.
*NOT RECOMMENDED FOR REFINED PETROLEUM PRODUCTS.



NITRILE BLEND

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	1.89"	100'	150	450	7"	.80	COS 100
2"	2.45"	100'	150	450	8"	1.00	COS 200
2-1/2"	3.00"	100'	150	450	10"	1.26	COS 250
3"	3.50"	100'	150	450	12"	1.80	COS 300
4"	4.55"	100'	150	450	15"	2.30	COS 400
6"	6.61"	20'	150	450	26"	5.00	COS 600
8"	8.70"	20'	150	450	35"	7.60	COS 800



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.