



**SEALFAST**  
THE SIMPLE SOLUTION

**HOSES**  
INDUSTRIAL RUBBER



PETROLEUM

## CRUDE OIL SUCTION CORRUGATED

### FEATURES & APPLICATIONS:

- Designed for oilfield vacuum truck service where extra flexibility is needed; tube & cover are crude oil resistant.
- Recommended for CRUDE OIL ONLY. \*NOT RECOMMENDED FOR REFINED PETROLEUM PRODUCTS.



### TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/NBR
- **Tube:** CR/NBR
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



### NITRILE BLEND

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
2"	2.64"	100'	150	450	8"	1.00	CCOS 200
3"	3.66"	100'	150	450	12"	1.80	CCOS 300
4"	4.76"	100'	150	450	15"	2.30	CCOS 400



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

[sales@Seal Fast.com](mailto:sales@Seal Fast.com)

800.231.0734

[Seal Fast.com](http://Seal Fast.com)

5603 Harvey Wilson Drive, Houston, TX