



SEALFAST
THE SIMPLE SOLUTION

HOSES
INDUSTRIAL RUBBER



AIR

GENERAL PURPOSE PREMIUM AIR HOSE

FEATURES & APPLICATIONS:

- An premium general purpose air & water hose engineered for medium duty applications [Limited Oil Resistance]

Size Range

BL = (5/8" & 3/4")

Y = (5/8" & 3/4")

G = (5/8" & 3/4")

B = (1/4" - 2")

R = (1/4" - 2")

TECHNICAL DATA:

- **Temp Range:** -20° F to +176° F
- **Cover:** EPDM/SBR blend
- **Tube:** EPDM/SBR blend
- **Reinforcement:** Spiral braided polyester
- **Safety Factor:** 3:1 min
- **Branding:**

NOTES:

*Part # X below = Color above



EPDM / SBR BLEND

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1/4"	.51"	600'	300	900	---	0.123	SFAHX 025*
3/8"	.65"	600'	300	900	---	0.163	SFAHX 038*
1/2"	.82"	600'	300	900	---	0.242	SFAHX 050*
5/8"	1.14"	300'	300	900	---	0.429	SFAHX 058*
3/4"	1.14"	300'	300	900	---	0.429	SFAHX 075*
1"	1.39"	300'	200	600	---	0.535	SFAHX 100 *
1"	1.44"	300'	300	900	---	0.537	SFAHX 100-2*
1"	1.39"	100'	200	600	---	0.535	SFAHX 100-100*
1-1/4"	1.73"	100'	200	600	---	0.813	SFAHX 125*
1-1/2"	2.05"	100'	200	600	---	1.123	SFAHX 150*
2"	2.64"	100'	200	600	---	1.22	SFAHX 200*