



**SEALFAST**  
THE SIMPLE SOLUTION

**HOSES**  
INDUSTRIAL RUBBER



**AIR**

## GENERAL PURPOSE PREMIUM AIR HOSE

### FEATURES & APPLICATIONS:

- An premium general purpose air & water hose engineered for medium duty applications [Limited Oil Resistance]



BL

Y

G

B

R

### TECHNICAL DATA:

- **Temp Range:** -20° F to +176° F
- **Cover:** EPDM/SBR blend
- **Tube:** EPDM/SBR blend
- **Reinforcement:** Spiral braided polyester
- **Safety Factor:** 3:1 min
- **Branding:**

\*Part # X = Color above



### EPDM / SBR BLEND

| ID     | OD    | Length      | Working Pressure | Burst Pressure | Bend Radius | lbs per ft. | Part #       |
|--------|-------|-------------|------------------|----------------|-------------|-------------|--------------|
| 1/4"   | .51"  | 600'        | 300              | 900            | ---         | 0.123       | SFAHX 025*   |
| 3/8"   | .65"  | 600'        | 300              | 900            | ---         | 0.163       | SFAHX 038*   |
| 1/2"   | .82"  | 600'        | 300              | 900            | ---         | 0.242       | SFAHX 050*   |
| 5/8"   | 1.14" | 300'        | 300              | 900            | ---         | 0.429       | SFAHX 058*   |
| 3/4"   | 1.14" | 300'        | 300              | 900            | ---         | 0.429       | SFAHX 075*   |
| 1"     | 1.39" | 100' / 300' | 200              | 600            | ---         | 0.535       | SFAHX 100 *  |
| 1"     | 1.44" | 300'        | 300              | 900            | ---         | 0.537       | SFAHX 100-2* |
| 1-1/4" | 1.43" | 100'        | 200              | 600            | ---         | 0.813       | SFAHX 125*   |
| 1-1/2" | 2.05" | 100'        | 200              | 600            | ---         | 1.123       | SFAHX 150*   |
| 2"     | 2.64" | 100'        | 200              | 600            | ---         | 1.22        | SFAHX 200*   |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.