



STEAM



FEATURES & APPLICATIONS:

- High pressure wire reinforced steam hose designed for service w/Super heated steam in heat control, fire prevention, thawing, etc., In many industries at max pressure of 17 ATM (250 psi).
- Pin Prick Cover, for longer life drain after use.
- * NOT RECOMMENDED FOR STEAM CLEANER

NOTES:



WARNING:

- Drain after use
- Steam heat increases in temperature as pressure increases
- Please consult with your coupling manufacture to insure the hose is coupled in accordance with current safety standards.
- Exposure to steam can cause serious injury or even death.
- Correct hose selection, assembly, maintenance and useage is critcial to avoid serious injury or even death.



TECHNICAL DATA:

- **Temp Range:** -40° F to +450° F
- **Cover:** Nitrile (pinpricked)
- **Tube:** Black, smooth, EPDM rubber specially compounded to withstand saturated & super-heated steam
- **Reinforcement:** Plies of steel wire cord
- **Safety Factor:** 10:1 min
- **Branding:**

BLACK NEOPRENE / NITRILE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1/2"	.99"	50' / 100'	250	n/a	6"	.37	ST 050
3/4"	1.25"	50' / 100'	250	n/a	9"	.52	ST 075
1"	1.50"	50' / 100'	250	n/a	12"	.65	ST 100
1-1/4"	1.80"	50' / 100'	250	n/a	15"	.83	ST 125
1-1/2"	2.12"	50' / 100'	250	n/a	18"	1.11	ST 150
2"	2.60"	50' / 100'	250	n/a	24"	1.50	ST 200
3"	2.60"	50' / 100'	250	n/a	24"	1.50	ST 300



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.