



SEALFAST
THE SIMPLE SOLUTION

HOSES
INDUSTRIAL RUBBER



WATER

BLENDED WATER SUCTION

FEATURES & APPLICATIONS:

- Designed to meet almost all water hose applications, especially designed for use in construction, mining, industrial, & agricultural service. It is flexible & with stands high vacuum.



TECHNICAL DATA:

- **Temp Range:** -22° F to +180° F
- **Cover:** Black, NR/SBR
- **Tube:** Black, NR/SBR
- **Reinforcement:** High tensile textile fabric; steel wire helix
- **Safety Factor:** 3:1 min
- **Branding:** Size Seal Fast WATER SUCTION 150 PSI WP



BLACK SBR / NATURAL RUBBER

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1"	1.37"	100'	150	450	5"	0.50	CWS 100 100
1-1/4"	1.65"	100'	150	450	5"	0.60	CWS 125 100
1-1/2"	1.89"	50' / 60' / 100'	150	450	6"	0.82	CWS 150 50
2"	2.44"	50' / 60' / 100'	150	450	8"	1.01	CWS 200 50
2-1/2"	3.00"	50' / 60' / 100'	150	450	10"	1.50	CWS 250 50
3"	3.55"	50' / 60' / 100'	150	450	12"	1.75	CWS 300 50
4"	4.57"	50' / 60' / 100'	100	300	16"	2.40	CWS 400 50
6"	6.61"	20' / 100'	100	300	24"	4.84	CWS 600 20
8"	8.70"	20' / 100'	100	300	32"	8.10	CWS 800 20



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.

sales@Seal Fast.com

800.231.0734

Seal Fast.com

5603 Harvey Wilson Drive, Houston, TX