



WATER

BLENDED WATER SUCTION



FEATURES & APPLICATIONS:

- Designed to meet almost all water hose applications, especially designed for use in construction, mining, industrial, & agricultural service. It is flexible & with stands high vacuum.

TECHNICAL DATA:

- **Temp Range:** -22° F to +180° F
- **Cover:** Black, NR/SBR
- **Tube:** Black, NR/SBR
- **Reinforcement:** High tensile textile fabric; steel wire helix
- **Safety Factor:** 3:1 min
- **Branding:** Size Seal Fast WATER SUCTION 150 PSI WP



BLACK SBR / NATURAL RUBBER

| ID | OD | Length | Working Pressure | Burst Pressure | Bend Radius | lbs per ft. | Part # |
|--------|-------|------------------|------------------|----------------|-------------|-------------|-------------|
| 1" | 1.37" | 100' | 150 | 450 | 5" | 0.50 | CWS 100 100 |
| 1-1/4" | 1.65" | 100' | 150 | 450 | 5" | 0.60 | CWS 125 100 |
| 1-1/2" | 1.89" | 50' / 60' / 100' | 150 | 450 | 6" | 0.82 | CWS 150 50 |
| 2" | 2.44" | 50' / 60' / 100' | 150 | 450 | 8" | 1.01 | CWS 200 50 |
| 2-1/2" | 3.00" | 50' / 60' / 100' | 150 | 450 | 10" | 1.50 | CWS 250 50 |
| 3" | 3.55" | 50' / 60' / 100' | 150 | 450 | 12" | 1.75 | CWS 300 50 |
| 4" | 4.57" | 50' / 60' / 100' | 100 | 300 | 16" | 2.40 | CWS 400 50 |
| 6" | 6.61" | 20' / 100' | 100 | 300 | 24" | 4.84 | CWS 600 20 |
| 8" | 8.70" | 20' / 100' | 100 | 300 | 32" | 8.10 | CWS 800 20 |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.