



WATER

WATER DISCHARGE

2 PLY



FEATURES & APPLICATIONS:

- A lightweight hose with a tough mandrel built construction, suitable for submersible pumps, irrigation & drainage systems, can be rolled up flat for storage.

TECHNICAL DATA:

- **Temp Range:** -22° F to +180° F
- **Cover:** Black, SBR/NR
- **Tube:** Black, SBR/NR
- **Reinforcement:** High tensile textile fabric
- **Safety Factor:** 3:1 min
- **Branding:**



BLACK EPDM RUBBER

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	1.93"	50' / 100'	150	450	n/a	.71	DH 150-2
2"	2.48"	50' / 100'	150	450	n/a	1.01	DH 200-2
2-1/2"	3.03"	50' / 100'	150	450	n/a	1.24	DH 250-2
3"	3.50"	50' / 100'	150	450	n/a	1.51	DH 300-2
4"	4.61"	50' / 100'	150	450	n/a	2.35	DH 400-2
6"	6.58"	50' / 100'	100	300	n/a	3.43	DH 600-2
8"	8.70"	50' / 100'	75	225	n/a	5.58	DH 800-2
10"	10.71"	50'	60	180	n/a	6.89	DH 1000-2
12"	12.72"	50'	40	120	n/a	8.23	DH 1200-2



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.