



**MATERIAL
TRANSFER**

HOT TAR

FEATURES & APPLICATIONS:

- Designed for transfer of high temperature asphalt, tar & hot oils.
- Compounded for long wear resistance in handling of hard, sharp, abrasive materials; anti-static.



TECHNICAL DATA:

- **Temp Range:** -20° F to +350° F
- **Cover:** Black Synthetic Acrylic Rubber
- **Tube:** Black CR Anti-Static Wrap
- **Reinforcement:** High Tensile Tire Cord; Helix Wire
- **Safety Factor:** 4:1 min
- **Branding:**

NOTES:

- Hose construction may vary. Hoses might be supplied with 1 or 2 wires. This does not affect working/burst pressure.



BLACK SYNTHETIC ACRYLIC RUBBER

ID	PLY	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
2"	---	2.71"	100' / 200'	150	600	10"	1.30	HTA 200
3"	---	4.63"	100' / 200'	150	600	15"	2.94	HTA 300
4"	---	4.79"	100' / 200'	150	600	20"	3.89	HTA 400



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.