



CHEMICAL

XLPE 200



FEATURES & APPLICATIONS:

- A premium hose w/Special compounded crosslinked polyethylene tube, handles a wide range of chemicals, solvents and corrosive liquids in both pressure and suction service.

TECHNICAL DATA:

- **Temp Range:** -40° F to +176° F
- **Cover:** Green, EPDM rubber abrasion & weather resistant
- **Tube:** Translucent, smooth cross-linked polyethylene
- **Reinforcement:** 3 ply polyester tire cord & steel helix wire
- **Safety Factor:** 4:1 min
- **Branding:** XLPE Chemical S/D xxx psi (yellow lettering)

* All specifications at 70° operating temperature.



GREEN EPDM / CROSS-LINKED POLYETHYLENE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
3/4"	1.26"	100'	200	800	3"	.54	CH 075
1"	1.50"	100'	200	800	4"	.67	CH 100
1-1/4"	1.78"	100'	200	800	6"	.81	CH 125
1-1/2"	2.01"	100'	200	800	7"	.94	CH 150
2"	2.52"	100'	200	800	10"	1.28	CH 200
2-1/2"	3.04"	100'	200	800	17"	1.55	CH 250
3"	3.55"	100'	200	800	18"	1.95	CH 300
4"	4.65"	100'	200	800	20"	2.76	CH 400

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.