



**CHEMICAL**

## UHMW

Ultra High Molecular Weight Chemical Hose

### FEATURES & APPLICATIONS:

- Handles 98% of common industrial chemicals in pressure, suitable for suction & discharge services. Exceptional flexibility.
- Available in green



### TECHNICAL DATA:

- **Temp Range:** -40° F to +250° F (Intermittent)
- **Cover:** Blue corrugated EPDM blend
- **Tube:** Clear Ultra High Molecular Weight Polyethglenc, EPDM
- **Reinforcement:** Heigh Tensile Textile cord + double steel helix wire
- **Safety Factor:** 4:1 min
- **Branding:** UHMW Chemical S/D 200 psi W.P. & White Stripe

\* All specifications at 70° operating temperature.



### BLUE EPDM / ULTRA HIGH MOLECULAR WEIGHT POLYTETHYLENE

ID	OD	Length	Working Pressure	Vacuum Rating	Bend Radius	lbs per ft.	Part #
1"	1.58"	100'	200	---	6"	.67	UHMW 100
1-1/4"	2.09"	100'	200	---	9"	.94	UHMW 125
1-1/2"	2.09"	100'	200	---	9"	.94	UHMW 150
2"	2.64"	100'	200	---	11"	1.28	UHMW 200
2-1/2"	2.64"	100'	200	---	11"	1.28	UHMW 250
3"	3.67"	100'	200	---	16"	1.88	UHMW 300
4"	4.69"	100'	200	---	31"	2.49	UHMW 400
6"	4.69"	100'	200	---	31"	2.49	UHMW 600



Information contained on this page is for general information purposes only. SealFast Inc. assumes no responsibility for errors or omissions for this product.