



HYDRAULIC

## HYDRAULIC R2

TWO WIRE 100R2AT -  
(high pressure)

### FEATURES & APPLICATIONS:

- Excellent for hydraulic based liquids
- Meets and exceeds SAE J517 100R2AT



### TECHNICAL DATA:

- **Temp Range:** -40° F to +212° F
- **Cover:** Oil & Weather Resistant Synthetic Rubber
- **Tube:** Oil & Weather Resistant Synthetic Rubber
- **Reinforcement:** 2 Steel Wire Braid
- **Safety Factor:** 4:1 min
- **Branding:** Size SAE 100R2AT XXXXPSI W.P. fxs 2015.05

### NOTES:

- Hose available on reel.

### OIL RESISTANT SYNTHETIC RUBBER

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
1/4"	0.61"	328' +/-	5000	20000	2.0"	23.5	---	R2AT-04BC
3/8"	0.75"	328' +/-	4000	16000	2.5"	30.9	---	R2AT-06BC
1/2"	0.88"	328' +/-	3500	14000	3.5"	42.3	---	R2AT-08BC
5/8"	1.00"	328' +/-	2750	11000	4.0"	51.1	---	R2AT-10BC
3/4"	1.16"	328' +/-	2250	9000	4.8"	63.2	---	R2AT-12BC
1"	1.42"	328' +/-	2000	8000	6.0"	80.6	---	R2AT-16BC
1-1/4"	1.92"	196' +/-	1625	6500	16.5"	114.0	---	R2AT-20BC
1- 1/2"	2.20"	196' +/-	1250	5000	20.0"	147.0	---	R2AT-24BC
2"	2.70"	196' +/-	1125	4500	25.0"	190.0	---	R2AT-32BC



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.