



MILL - SINGLE JACKET
SBR LINED

MILL



FEATURES & APPLICATIONS:

- All synthetic, lightweight SBR (rubber) lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.

TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** SBR
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-SBR LINED

ID	OD	Length	Working Pressure	Burst Pressure	Lbs per Roll	Part #
1"	n/a	50'	150	450	8	80-100
1-1/2"	n/a	50' / 100'	150	450	11 / 22	80-150 / 80-150 100
2"	n/a	50' / 100'	150	450	17 / 34	80-200 / 80-200 100
2-1/2"	n/a	50' / 100'	150	450	20 / 40	80-250 / 80-250 100
3"	n/a	50' / 100'	150	450	28 / 56	80-300 / 80-300 100
4"	n/a	50'	150	450	50	80-400 / 80-400 100

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.