



MILL - SINGLE JACKET PVC-NBR LINED

FEATURES & APPLICATIONS:

- All synthetic, lightweight PVC / NBR (plastic/rubber) lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** PVC/NBR
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-PVC/NBR LINED

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
1"	n/a	50' / 100'	150	450	n/a	8 / 16	n/a	80-100PN / 80-100PN 100
1-1/2"	n/a	50' / 100'	150	450	n/a	11 / 22	n/a	80-150PN / 80-150PN 100
2"	n/a	50' / 100'	150	450	n/a	17 / 34	n/a	80-200PN / 80-200PN 100
2-1/2"	n/a	50' / 100'	150	450	n/a	20 / 40	n/a	80-250PN / 80-250PN100
3"	n/a	50' / 100'	150	450	n/a	28 / 56	n/a	80-300PN / 80-300PN 100
4"	n/a	50' / 100'	150	450	n/a	50	n/a	80-400PN / 80-400PN 100



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.