



MILL - SINGLE JACKET
PVC-NBR LINED

MILL



FEATURES & APPLICATIONS:

- All synthetic, lightweight PVC / NBR (plastic/rubber) lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.

TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** PVC/NBR
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-PVC/NBR LINED

ID	OD	Length	Working Pressure	Burst PSI	Lbs per Roll	Part #
1"	n/a	50' / 100'	150	450	8 / 16	80-100PN / 80-100PN 100
1-1/2"	n/a	50' / 100'	150	450	11 / 22	80-150PN / 80-150PN 100
2"	n/a	50' / 100'	150	450	17 / 34	80-200PN / 80-200PN 100
2-1/2"	n/a	50' / 100'	150	450	20 / 40	80-250PN / 80-250PN100
3"	n/a	50' / 100'	150	450	28 / 56	80-300PN / 80-300PN 100
4"	n/a	50' / 100'	150	450	50	80-400PN / 80-400PN 100

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.