



MILL - SINGLE JACKET
EPDM LINED

FEATURES & APPLICATIONS:

- All synthetic, lightweight EPDM Rubber lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** EPDM
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-EPDM LINED

ID	OD	Length	Working Pressure	Burst Pressure	Lbs per Roll	Part #
1"	n/a	50'	150	450	8	80-132
1-1/2"	n/a	50' / 100'	150	450	11 / 22	80-133 / 80-133 100
2"	n/a	50' / 100'	150	450	17 / 34	80-134 / 80-134 100
2-1/2"	n/a	50' / 100'	150	450	20 / 40	80-135 / 80-135 100
3"	n/a	50' / 100'	150	450	28 / 56	80-136 / 80-136 100
4"	n/a	50'	150	450	50	80-137
6"	n/a	50'	150	450	59	80-139

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.