



MILL - SINGLE JACKET
EPDM LINED

FEATURES & APPLICATIONS:

- All synthetic, lightweight EPDM Rubber lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** EPDM
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

POLYESTER-EPDM LINED

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
1"	n/a	50'	110	n/a	n/a	8	---	80-132
1-1/2"	n/a	50' / 100'	110	n/a	n/a	11 / 22	---	80-133 / 80-133 100
2"	n/a	50' / 100'	110	n/a	n/a	17 / 34	---	80-134 / 80-134 100
2-1/2"	n/a	50' / 100'	110	n/a	n/a	20 / 40	---	80-135 / 80-135 100
3"	n/a	50' / 100'	110	n/a	n/a	28 / 56	---	80-136 / 80-136 100
4"	n/a	50'	110	n/a	n/a	50	---	80-137
6"	n/a	50'	110	n/a	n/a	59	---	80-139

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.