



**MILL - DOUBLE JACKET**  
SBR LINED

MILL



**FEATURES & APPLICATIONS:**

- All synthetic, lightweight SBR (rubber) lined general purpose hose designed for open end discharge and wash down. This hose is totally immune to the effects of mildew and requires no drying.

**TECHNICAL DATA:**

- **Temp Range:** -22° F to +158° F
- **Cover:** Double Jacket White Polyester
- **Tube:** SBR
- **Safety Factor:** n/a
- **Branding:**

**NOTES:**

- Made over sized to accommodate shank couplings.
- Not intended for use as Firehose

**POLYESTER-SBR LINED**

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
1-1/2"	n/a	50' / 100'	220	n/a	n/a	11 / 22	---	80-150DJ / 80-150DJ 100
2"	n/a	50' / 100'	220	n/a	n/a	28 / 56	---	80-300DJ / 80-300DJ 100
2-1/2"	n/a	50' / 100'	220	n/a	n/a	50 / 56	---	80-400DJ / 80-400DJ 100

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.