



FIRE - SINGLE JACKET

EPDM LINED - 300# Test - UL Label

FEATURES & APPLICATIONS:

- Single Jacket with a high-grade single ply extruded EPDM liner. This hose is totally immune to the effects of mildew. It is designed for emergency fire protection with water pressure not exceeding 135 psi working pressure. 100% Polyester Cover.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Single Jacket White Polyester
- **Tube:** EPDM
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Maximum advised operating/working pressure that should not exceed 90% of Service Test Pressure (Stenciled on hose) 150 psi

*Service Test Pressure are 1/2 of Acceptance Test Pressure Per NFPA 1962

POLYESTER-EPDM LINED

ID	OD	Length	Working Pressure	Service Test Pressure	Bend Radius	Lbs per Roll	Bowl Size	Part #
1-1/2"	n/a	50'/75'/100'	135	150	n/a	11/17/22	1-3/4"	80-075UL / 80-075UL 75 / 80-075UL 100
2-1/2"	n/a	50'/75'/100'	135	150	n/a	25/38/50	2-13/16"	80-077UL / 80-077UL 75 / 80-077UL100



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.