




VALVES

Y-STRAINER - 316 SS
800 WOG/CWP

FEATURES & APPLICATIONS:

- 800 WOG/CWP
- Body & Cap; ASTM A351-CF8M
- Screen; S/S304 20 Mesh
- Hole Size 1.0mm
- NPT Thread




TECHNICAL DATA:

- **WOG** = Rating indicates the maximum non-shock pressure at ambient temperatures at which the valve may be used.
- **CWP** = Cold working pressure

WOG: Water, Oil & Gas: This was an older, generic pressure rating call-out which has been largely replaced by CWP. In this designation, "GAS" refers to any non-flammable, compressible fluid in a gaseous state. It does not imply a product's suitability or third-party approval for use with flammable gases. Similarly, in this designation, "Oil" does not imply a product's third-party approval for use with any petroleum products.

316 SS

Size	Part #
1/2"	YS050SS
3/4"	YS075SS
1"	YS100SS
1-1/4"	YS125SS
1-1/2"	YS150SS
2"	YS200SS



Dimensions						
Size	A	B	C	F	SW	Part #
1/2"	1.54	2.20	.51	.47	.96	YS050SS
3/4"	1.85	2.71	.79	.47	1.30	YS075SS
1"	1.97	2.99	.79	.55	1.52	YS100SS
1-1/4"	2.56	2.52	1.06	.61	1.85	YS125SS
1-1/2"	2.91	4.01	1.26	.75	2.11	YS150SS
2"	3.46	4.72	1.65	.75	2.64	YS200SS

Nomenclature & Material		
No.	Description	Material
1	Body	316 SS
2	Filter	304 SS
3	Seal	PTFE
4	Cap	316 SS

TITLE **Y-STRAINER VALVE**

DISCLAIMER

All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast Inc. cannot guarantee the dimensions will exactly match those in the drawing. The drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

MATERIAL

316 SS

DRAWING NOT TO SCALE

PART #

YS...SS