

## PIPE FITTINGS



**VALVES** 

BALL - BRASS UL 600 WOG/CWP

#### **FEATURES & APPLICATIONS:**

- Standard Port 2 Piece
- UL 600 WOG/CWP
- Plumbing or heating projects, low pressure steam, compressed air, HVAC



#### **TECHNICAL DATA:**

- **WOG** = Rating indicates the maximum non-shock pressure at ambient temperatures at which the valve may be used.
- CWP = Cold working pressure

**WOG:** Water, Oil & Gas: This was an older, generic pressure rating call-out which has been largely replaced by CWP. In this designation, GAS" refers to any non-flammable, compressible fluid in a gaseous state. It does not imply a product's suitability or third-party approval for use with flammable gases. Similarly, in this designation, "Oil" does not imply a product's third-party approval for use with any petroleum products.

BRASS					
Size	Part #				
1/4"	BFV 025				
3/8"	BFV 038				
1/2"	BFV 050				
3/4"	BFV 075				
1"	BFV 100				
1-1/4"	BFV 125				
1-1/2"	BFV 150				
2"	BFV 200				


Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.




### PIPE FITTINGS







Dimensions							
Size	G	В	Н	D	L	Part #	
1/4"	1/4" NPT	3.15	1.50	.35	1.57	BFV 025	
3/8"	3/8" NPT	3.15	1.61	.39	1.52	BFV 038	
1/2"	1/2" NPT	3.54	1.81	.55	1.87	BFV 050	
3/4"	3/4" NPT	3.54	2.13	.75	2.17	BFV 075	
1"	1" NPT	4.33	2.17	.87	2.44	BFV 100	
1-1/4"	1-1/4" NPT	5.12	2.56	1.14	2.91	BFV 125	
1-1/2"	1-1/2" NPT	5.43	2.95	1.46	3.31	BFV 150	
2"	2" NPT	7.13	3.35	1.77	3.86	BFV 200	



# DISCLAIMER All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast cannot guarantee the dimensions of the part will exactly match those in the drawing. This drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited. DRAWING NOT TO SCALE MATERIAL MATERIAL BRASS

BALL VALVE - UL 600 WOG/CWP

